



* Front grille and mounting bracket have been painted to match the ceiling

Key Features

- Ready for "Plug-and-Play" installation
- Advanced electronic control system
- 55°F temperature differential
- Front grille and mounting bracket are paintable
- Built-in condensate pump
- Liquid temperature bottle probe
- With remote control
- Built-in cold weather start kit on condensing unit

Specifications

Model	CM2500-CR	CM3500-CR	CM5000-CR
Cellar Size (cu. ft.)	500	1000	2000
BTU/h (w/85°F air entering the condenser coil)	2167	4000	5254
CFM	107	321	
Dimensions	11.08" H x 11.34" W x 22.05" D	12.75" H x 14.5" W x 35.75" D	
Refrigerant	R-134a		
HP	1/6	1/3++	
Voltage Rating	110V (20 amp dedicated circuit required)		
Weight (lbs)	40.6	80	
Amps (LRA/RLA)	2/1	2/1	
dBA (Evaporator)	52	58.5	
Line Set	Please refer to the technician's manual		
Drainline	1/4" ID clear plastic tubing		
Installation	Evaporator is installed in the cellar. Condensing is installed up to 100 line ft. away in accordance with the installation specifications found in the technician's manual. Allow for adequate airflow.		
Thermostat	Remote digital display with 50-ft. cable and 50-ft. bottle probe		
Temp. Delta	55°F temperature differential between the cellar and condensing unit intake temperature		
Suggested Condenser	Copeland: M7JH-0014	Copeland: M7EH-H041	Copeland: M7EH-H046
Warranty	Two-year limited warranty (parts and labor)		

CR units come with the Evaporator, Controller & Bottle Probe. The Condenser is supplied and warranty by others. The condenser size must be matched with the proper size CellarCool Evaporator for the system to work properly. The wrong match will void the warranty.