



Key Features

- Air Handler mounts up to 50ft. away for quiet in cellar enjoyment
- Ideal for larger cellars or cellars with large amount of glass windows
- Multiple supply ducting options, making it adaptable to almost any installation
- Designed to operate in frigid climates as low as -15 degrees
- Advanced electronic control with digital remote keypad for a user friendly experience
- Bottle probe for measuring liquid temperature
- Includes a condensate pump system
- Built-in cold weather start kit on condensing unit (9000 only)

Specifications

Model	Magnum SS9000	Magnum SS12000
Cellar Size (cubic feet)	3000*	4000*
BTU/h (w/85°F air entering the condenser coil)	9572	12530
CFM	Evaporator: 810	
Dimensions	Evaporator: 29.5"L x 30.9"W x 19.8"H • Condenser: 24"L x 18.98"W x 16.16"H	
Refrigerant	R-134a	
HP	3/4	1 1/4
Voltage Rating	Evaporator: 115V (15 amp dedicated circuit required) Condenser: 230V (15 amp dedicated circuit required)	Evaporator: 115V (15 amp dedicated circuit required) Condenser: 230V (20 amp dedicated circuit required)
Weight (lbs)	Evaporator: 133 • Condenser: 95	Evaporator: 133 • Condenser: 95
Amps	Evaporator: 3.2 (running amps) Condenser: LRA 35/RLA 6.5	Evaporator: 3.2 (running amps) Condenser: LRA 56/RLA 12
Line Set	Liquid Line 3/8" • Suction Line (Less than 50ft. 3/4") (Greater than 50ft. 7/8")	Liquid Line 3/8" • Suction Line 7/8"
Drain Line (ID)	3/4" ID CPVC	
Installation	Evaporator can be installed up to 25 duct feet away from the cellar. Condensing unit can be installed up to 100	
Thermostat	Advanced digital display (50ft. cable), liquid-temperature-measuring bottle probe (50ft. cable)	
Temp. Delta	Can maintain a 55°F cellar temperature with up to 110°F condenser air intake temperature	
Warranty	Two-year limited warranty (parts and labor). Technician MUST return charging records to CellarCool to validate warranty.	

*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

Optional Accessories

Exterior condenser housing, 24V thermostat conversion kit, condenser coil coating