



## Key Features

- Direct replacement for Breezair and Wine Mate
- Dynamic airflow
- 30°F temperature differential
- Flexible mounting bracket
- Advanced digital controller
- Built-in air sensor

## Specifications

Model	CX2200/CX2200-RPC	CX3300/CX3300-RPC	CX4400/CX4400-RPC	CX8800/CX8800-RPC
Cellar Size (cu. ft.)	300*	650*	1000*	2000*
BTU/h (w/85°F air entering the condenser coil)	1453	2049	2962	4754
CFM	118	126	216	374
Dimensions	16.38"L x 14.25"W x 13.25"H	21.63"L x 14.25"W x 19.75"H		22.25"L x 16.25"W x 22"H
Refrigerant	R-134a	R-134a	R-134a	R-134a
HP	0.57	0.8	1.16	1.86
Voltage Rating	115V (20 amp dedicated circuit required)			
Weight (lb.)	65	66	67	74
Amps	4.5 (running amps)	4.9 (running amps)	9 (running amps)	10 (running amps)
dBA (Evaporator/Condenser)	63 / 63	63 / 64	63 / 64	68 / 68
Drain Line	3/8" Condensate (rear location only)			
Installation	Through-the-wall, partially ducted			
Thermostat	Advanced digital display			
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature			
Warranty	2-year parts and labor / 5-year compressor			

RPC — Rear Power Cord

\*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.