



## Key Features

- Advanced blower fans
- Quiet operation
- Condensate evaporator
- TXV expansion valve
- Liquid-temperature-measuring Bottle Probe
- Digital controller on face of unit
- Coated evaporator coil
- Front or rear power

## Specifications

Model	2200	3300	4400	8800
Cellar Size (cu. ft.)	300*	650*	1000*	1500*
BTU/h (w/85°F condenser air intake temperature)	1453	2049	2253	4241
Dimensions	17.5"L x 14.25"W x 15.75"H			21.64"L x 14.25"W x 22.56"H
Refrigerant	R-134a			
HP	1/8	1/6	1/6+	1/2
Voltage Rating	115V (15 amp dedicated circuit required)			115V (20 amp dedicated circuit required)
Weight (lb.)	65			104
Amps	3.2 (running amps)	3.7 (running amps)	4.7 (running amps)	10.9 (running amps)
Drain Line	½" Condensate (rear location only)			
Installation	Through-the-wall, partially ducted			
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)			
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature			
Ducting Options	Exhaust air can be ducted using the optional ducting kit			
Warranty	2-year parts and labor / 5-year compressor			

\*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

## Optional Accessories

Exhaust ducting kit, exterior housing