



Key Features

- Variable-speed fans
- Operates in extreme environments
- 55°F temperature differential
- Flexible mounting bracket
- Control mounted on front of unit or remote
- Ductable exterior exhaust
- Bottle probe measures liquid temperature

Specifications

| Model | Ultimate 3300/Ultimate 3300-R | Ultimate 4400/ Ultimate 4400-R | Ultimate 8800/ Ultimate 8800-R |
|---|--|--------------------------------|--------------------------------|
| Cellar Size (cu. ft.) | 800 | 1250 | 2000 |
| BTU/h(w/85°F air entering the condenser coil) | 2688 | 4200 | 5760 |
| CFM | 256 | 256 | 283 |
| Dimensions | 14.25"W x 15.75"H x 26"D | | 16.25"W x 22"H x 27.5"D |
| Refrigerant | R-134a | R-134a | R-134a |
| HP | ¼+ | ¼+ | ¾+ |
| Voltage Rating | 110V (20 amp dedicated circuit required) | | |
| Weight (lb.) | 115 | 115 | 150 |
| Amps (Starting/Running) | 32 / 9 | 32 / 9 | 36 / 17 |
| dBA (Low/Medium/High) | 51 / 58 / 66 | 51 / 58 / 66 | 57 / 59 / 61 |
| Drain Line | ½" Condensate | | |
| Installation | Through the wall, partially ducted, fully ducted | | |
| Thermostat | Advanced electronic control system | | |
| Temp. Delta | 55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F) | | |
| Outside Venting | Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended | | |
| Ducting Options | Unit can be fully ducted | | |
| Warranty | 2-year parts and labor | | |

R — Remote control

Optional Accessories

Ducting plenum, exterior grille