



### Key Features

- Variable-speed fans
- Operates in extreme environments
- 55°F temperature differential
- Flexible mounting bracket
- Control mounted on front of unit or remote
- Ductable exterior exhaust
- Bottle probe measures liquid temperature

### Specifications

Model	Ultimate 3300/Ultimate 3300-R	Ultimate 4400/ Ultimate 4400-R	Ultimate 8800/ Ultimate 8800-R
Cellar Size (cu. ft.)	800	1250	2000
BTU/h(w/85°F air entering the condenser coil)	2688	4200	5760
CFM	256	256	283
Dimensions	14.25"W x 15.75"H x 26"D		14.45"W x 22"H x 27.5"D
Refrigerant	R-134a	R-134a	R-134a
HP	¼+	¼+	¾+
Voltage Rating	110V (20 amp dedicated circuit required)		
Weight (lb.)	115	115	150
Amps (Starting/Running)	32 / 9	32 / 9	36 / 17
dBA (Low/Medium/High)	51 / 58 / 66	51 / 58 / 66	57 / 59 / 61
Drain Line	½" Condensate		
Installation	Through the wall, partially ducted, fully ducted		
Thermostat	Advanced electronic control system		
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)		
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended		
Ducting Options	Unit can be fully ducted		
Warranty	2-year parts and labor		

R — Remote control

### Optional Accessories

Ducting plenum, exterior grille