



* Front grille and mounting bracket have been painted to match the ceiling

Key Features

- Ready for “Plug-and-Play” installation
- Advanced electronic control system

- 55°F temperature differential
- Front grille and mounting bracket are paintable
- Liquid bottle probe & condensate pump included
- Built-in cold weather start kit on condensing unit

Specifications

Cellar Size	3000 cu. ft.*
BTU/h (85°F condenser air intake temperature)	Med: 7650 • High: 8500
CFM	308
Dimensions	Evaporator: 35.75”L x 12.75”H x 14.5”W (x2), w/mounting bracket: 38.75”L x 17.10”H (x2) Condenser: 16.08”L x 16.23”W x 12.61”H
Refrigerant	R-134a
HP	3.34
Voltage Rating	Evaporator: 115V (15 amp dedicated circuit required) • Condenser: 230V (15 amp dedicated circuit required)
Weight (lbs)	Evaporator: 80 (per unit) • Condenser: 67
Amps	Evaporator: 1 (running amps) (per unit) • Condenser: LRA 43/RLA 8
Line Set	Liquid Line 3/8” • Suction Line (Less than 50ft. 3/4”) (Greater than 50ft. 7/8”)
Drain Line	¼” ID clear plastic tubing (not provided)
Installation	Evaporator is installed in the cellar. Condensing unit can be installed up to 100 line feet from evaporator unit.
Thermostat	Advanced digital display (50ft. cable), liquid-temperature-measuring bottle probe (50ft. cable)
Temp. Delta	Can maintain a 55°F cellar temperature with up to 110°F condenser air intake temperature
Warranty	Two-year limited warranty (parts and labor)

*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

Optional Accessories

Exterior condenser housing, 24V thermostat conversion kit, condenser coil coating