



## Key Features

- Advanced blower fans
- Quiet operation
- Condensate evaporator
- TXV expansion valve
- Liquid-temperature-measuring Bottle Probe
- Digital controller on face of unit
- Coated evaporator coil
- Front or rear power
- UV-C Lighting System

## Specifications

Model	2200	3300	4400	8800
Cellar Size (cu. ft.)	300*	650*	1000*	1500*
BTU/h (w/85°F condenser air intake temperature)	1453	2049	2253	4241
Dimensions	17.5"L x 14.25"W x 15.75"H			21.64"L x 14.25"W x 22.56"H
Refrigerant	R-134a			
HP	1/8	1/6	1/6+	1/2
Voltage Rating	115V (20 amp dedicated circuit required); 230V (subject to availability)			
Weight (lb.)	65			104
Amps	3.2 (running amps)	3.7 (running amps)	4.7 (running amps)	10.9 (running amps)
Drain Line	½" Condensate (rear location only)			
Installation	Through-the-wall, partially ducted			
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)			
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature			
Ducting Options	Exhaust air can be ducted using the optional ducting kit			
Warranty	2-year parts and labor / 5-year compressor			

\*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

## Optional Accessories

- Exhaust ducting kit
- Exterior housing
- UV-C Lighting System