



Key Features

- Greater cooling capacity
- Dual evaporators
- No ducting required
- Standard and 24V thermostat options available
- Bottle probe measures liquid temperature
- Flexible installation options
- 55°F temperature differential between cellar environment and condensing unit intake air

Specifications

Model	WM9000Twin-S	WM9000Twin-S-24V
Cellar Size (cu. ft.)	3000*	
BTU/h (w/85°F air entering the condenser coil)	Low: 7536 • Med: 7850 • High: 8164	
CFM	200 (per unit)	
Dimensions	Evaporator: 16.1"L x 20.5"W x 15.5"H (x2) • Condensing Unit: 24"L x 18.98"W x 16.16"H	
Refrigerant	R-134a	
Voltage Rating	Evaporator: 115V (15 amp dedicated circuit required) • Condenser: 230V (15 amp dedicated circuit required)	
Weight (lbs)	Evaporators: 60 (per unit) • Condensing Unit: 95	
Amps	Evaporator: 1 running amps (per unit), Compressor: LRA 35 , RLA 6.5	
Drain Line	½" ID clear plastic tubing 'not included'	
Installation	Evaporator is installed in the cellar. Condensing unit can be installed up to 100 line feet from evaporator unit.	
Thermostat	Advanced digital display (50ft. cable), liquid-temperature-measuring bottle probe (retractable cable)	
Temp. Delta	Can maintain a 55°F cellar temperature with up to 110°F condenser air intake temperature	
Warranty	Two-year limited warranty (parts and labor). Technician MUST return charging records to CellarCool to validate warranty.	

*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

Optional Accessories

Exterior condenser housing, 24V thermostat conversion kit, condenser coil coating, UV-C Lighting System